

The unique UV-C disinfection unit Soluva® Air F cleans viruses, bacteria, and other pathogens from the room air reliably and quietly. With its high air flow rate, it provides fast and reliable protection — with a tested virus reduction of 99.99%. Soluva® Air F is already proving its worth in numerous offices and meeting rooms — and also in cafés and restaurants, in medical practice waiting rooms and in retail stores.























Simple and safe operation



**F** for flexible: The mobile and lightweight device is easy to set up anywhere in the room, mounting on the wall or on a mobile stand and can rotate in all directions. It is designed to operate continuously and quietly so it is barely noticed in daily office use.

**Less is more:** Unlike comparable air purification devices, Soluva® Air F is completely chemical-free, works without ozone or other by-products, and operates filter-free, so there are no expensive regular filter changes.

## Your benefits at a glance:

- + Best protection: safe inactivation of all germs, including Covid-19 viruses (test result: 99.99%)
- + Powerful: continuously adjustable air flow rate up to 1050 m<sup>3</sup>/h, suitable for continuous operation.
- + Optimal design: light weight, easy and very quiet operation
- + Economical and maintenance-free: no filters (no expensive filter replacement), long lamp life
- + Flexible: easy wall mounting or use on mobile stand
- + Quality and safety: developed by Heraeus in Germany



UV light at wavelengths from 200 to 300 nm splits the RNA/DNA of viruses, such as the coronavirus, and other microorganisms and thus produces strong disinfecting effect.

This is also proven by a Fraunhofer Institute for Building Physics IBP study. The institute confirms highly effective air purification and a massive reduction of the virus load by 99% – simulated under realistic conditions in a classroom. Even virus mutations are reliably destroyed.

Soluva® Air F	
Dimensions L × W × D	1000 × 876 × 220 mm
Weight	25 kg
Material	Aluminum, stainless steel
Air flow rate	300 to 1050 m³/h, infinitely variable
Dose	Log 3,92 @ 500 m³/h
Effective dose	>100 J/m²
Risk group (UV exposure)	Level 0 / free group
Noise 250 m³/h¹	≈ 30 db(A)
Noise 500 m³/h¹	≤ 40 db(A)
Noise 1050 m³/h¹	≤ 57 db(A)
Mounting	Wall mounting or mobile stand
UV lamp	Low-pressure mercury emitter
Wavelength	254 nm
Expected useful life <sup>2</sup>	approx. 12.000 h

<sup>1)</sup> Emission sound pressure level LpA in dB(A) at 1 meter distance.

## www.soluva.com

## Heraeus Noblelight GmbH

Heraeusstr. 12–14 63450 Hanau, Germany Phone: +49 6181 35 5522 service@heraeus-soluva.com Italy: +39 02 95759 212

Spain: +34 933 208 042 France: +33 1 6918 4851

Great Britain: +44 1295 272666

USA

## Heraeus Noblelight America LLC

910 Clopper Road Gaithersburg, MD 20878 Phone +1 240 690 3300 soluva.hna@heraeus.com

Please note that all information regarding the products and their properties may vary. 2022/01

<sup>2)</sup> Increased service life due to special glass coating. Advantages: more safety, longer maintenance intervals, lower costs. Equivalent to about 4 years at a daily operating time of 8 h.