Why Choose Nordson?

PureFlow™ Hoses with RediFlex™ II Mounts

Nordson BLUE, now available in SILVER™



Feature	Why is this Important?	Nordson PureFlow Hose	Competitor Hose
Reduced material degradation	Degradation can take the form of discoloration, change in odor, char formation, and change in viscosity and flow behavior. These changes can lead to poor adhesive application and product performance—even unplanned downtime.	Drastically reduces curing, charring, discoloration and odor related to degradation	See results below
Longer useful life	Adhesive degradation may lead to frequent hose replacements due to material buildup in the interior of the hose	Can double the life of an average hose in situations where degradation drives replacement*	
Easy snap-on installation	Enable flexible hose hanging, routing, pairing and keep hoses off of floors	Uses the RediFlex II mounting system	No feature

Hours in Hose at 350° F Setpoint*

0 8 16 24 32 40 48 72 96

Competitor's "No-Char" Hose

PureFlow™ Hose

To create these samples, each hose was filled with the same adhesive, then capped off and held at a consistent temperature. At the indicated times, the hose was uncapped, an adhesive sample was removed (shown), and the hose was recapped.

For more information, talk with your Nordson representative or contact your Nordson regional office.

United States Canada **Europe** Japan Asia/Australia/Latin America Duluth, Georgia Markham, Ontario Amherst, Ohio Erkrath, Germany Tokyo, Japan Telephone: 800.683.2314 Telephone: 800.463.3200 Telephone: 49.211.9205.0 Telephone: 81.3.5762.2710 Telephone: 440.985.4797 Facsimile: 866.667.3329 Facsimile: 905.475.8821 Facsimile: 49.211.254.658 Facsimile: 81.3.5762.2717 Facsimile: 440.985.1096







^{*}Actual results may vary